This machine and many others can be found at *hadanichmachine.com*!

| Category | Lathes - Shaft Type | |
|---|---------------------------------------|-------------|
| Manufacturer | Kramatorsk | |
| Model | 1A66O.400 | |
| Serial Number | 709 | |
| Year | 1989 | |
| Control | Digital Readout or Full CNC | |
| Swing Over Bed | 56.25 in | 1428.75 mm |
| Swing Over Cross Slide | 40.75 in | 1035.05 mm |
| Distance Between Centers | 320.00 in | 8128.00 mm |
| Swiveling Compound Angle Slide Travel | 8.00 in | 200.00 mm |
| Top Cross Slide Travel | 16.00 in | 400.00 mm |
| X – Cross Slide Travel | 39.37 in | 1000.00 mm |
| Z – Carriage Travel | 300.00 in | 7620.00 mm |
| Large Steady Rest Opening (Excluding Rollers Or Wear Pads) | 25.50 in | 650.00 mm |
| Small steady rest opening (Excluding rollers or wear pads) | 14.90 in | 380.00 mm |
| Chuck Diameter | 49.00 in | 1244.60 mm |
| Spindle Power | 150.00 HP | 111.85 kW |
| Tailstock Quill Diameter | 0.24 in | 6.10 mm |
| Weight Capacity Between Centers | 70000.00 lbs | 31751.44 kg |
| Chuck Type | Faceplate with 4 Bolt-On Hard Jaws | |
| Spindle Speed | 1.60 – 200.00 RPM Infinitely Variable | |
| Tailstock | Powered Tailstock | |

| Chip Conveyor | Optional | | |
|----------------|--|-------------|--|
| Coolant | Optional | | |
| Ways | Cast Iron | | |
| Power | As Needed | | |
| Additional | Dual cross slides, two closed three-point steady rests with changeable end contacts, also two adjustable half steady roller rests maximum diameter 40 inch (1016 mm) | | |
| Machine Length | 592.00 in | 15036.80 mm | |
| Machine Width | 83.50 in | 2120.90 mm | |
| Machine Height | 94.50 in | 2400.30 mm | |
| Weight | 95700.00 lbs | 43408.75 kg | |
| Condition | Excellent | | |